



● POWER WIRING INTERFACE POINTS
 ○ CONTROL WIRING INTERFACE POINTS
 * ALL CONTROL WIRING IS DISCRETIONARY
 ITEMS MARKED (\$) ARE EXTRA COST OPTIONS

ADJUSTABLE TARGET OUTPUT VOLTAGE (\$)

CONTROL BOARD

LCD DISPLAY

REMOTE ALARM CONTACT*
 0.6A @ 125VAC
 0.6A @ 110VAC
 2.0A @ 30VDC

| | | |
|---|--------------------------|---|
| Utility Systems Technologies, Inc. PO Box 110, Latham New York 12110 | | |
| TITLE: STD 3 PH ISOLATION XFMR SURE-VOLT ELECTRICAL SCHEMATIC WITH OPTIONS | | |
| REV: 2 DATE: January 22, 2009 REV: 1 DATE: AUGUST 15, 2008 REV: 0 DATE: DECEMBER 03, 2007 | SIZE: A | DWG NO.: EVR-0000-000D-000 |
| SCALE: NONE | SHEET: 1 OF 1 | REV: 1 |

PROPRIETARY AND CONFIDENTIAL - THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF UTILITY SYSTEMS TECHNOLOGIES, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF UTILITY SYSTEMS TECHNOLOGIES, INC. IS PROHIBITED